

**INDEPENDENT THREE PHASE 415Vac AUTOMATIC VOLTAGE STABILIZERS**

<b>MODEL</b>	<b>CABINET</b>	<b>RATED OUTPUT (KVA)</b>	<b>INPUT VARIATIONS</b>	<b>RATED CURRENT(A)</b>	<b>DIMENSIONS HxWxD(cm)</b>	<b>WEIGHT (Kg)</b>
CET-3-B	2	3	±15%	4.2	57.5 x27.0 x56.0	61.9
CET-6-B	2	6	±15%	8.3	57.5 x27.0 x56.0	72.3
CET-10-B	2	10	±15%	13.9	57.5 x27.0 x56.0	73.0
CET-15-B	1	15	±15%	20.9	120.0 x43.0 x36.0	125.0
CET-20-B	1	20	±15%	27.8	120.0 x51.0 x43.0	157.6
CET-30-B	1	30	±15%	41.7	120.0 x51.0 x43.0	168.0
CET-40-B	1	40	±15%	55.6	120.0 x57.5 x46.0	198.0
CET-50-B	1	50	±15%	69.5	120.0 x57.5 x46.0	222.0
CET-60-B	1	60	±15%	83.4	120.0 x60.0 x70.0	343.0
CET-75-B	1	75	±15%	104.3	120.0 x60.0 x70.0	359.0
CET-100-B	1	100	±15%	139.1	150.0 x60.0 x70.0	464.0
CET-125-B	1	125	±15%	174.0	150.0 x60.0 x70.0	475.0
CET-150-B	1	150	±15%	208.7	165.0 x70.0 x80.0	645.0
CET-200-A	2	200	±10%	278.2	107.0 x76.5 x130.0	660.0
CET-250-A	2	250	±10%	347.8	107.0 x76.5 x130.0	685.0
CET-300-A	2	300	±10%	417.4	107.0 x76.5 x130.0	880.0

**THREE PHASE 380Vac AUTOMATIC VOLTAGE STABILIZERS**

<b>MODEL</b>	<b>CABINET</b>	<b>POWER RATING (KVA)</b>	<b>INPUT VARIATIONS</b>	<b>RATED CURRENT</b>	<b>DIMENSIONS HxWXD(cm)</b>	<b>WEIGHT (kg)</b>
CET-12-D	2	12	± 25%	18.2	24.5 x 76.5 x 48.0	99.0
CET-15-D	2	15	± 25%	22.7	27.0 x 81.0 x 57.0	120.0
CET-22.5-D	2	22.5	± 25%	34.0	27.0 x 81.0 x 57.0	147.0
CET.30-D	1	30	± 25%	45.4	50.0 x 120.0 x 37.0	162.0
CET-45-D	1	45	± 25%	68.2	95.0 x 120.0 x 37.0	306.0
CET-60-D	1	60	± 25%	90.9	95.0 x 120.0 x 37.0	339.0
CET-75-B	1	75	± 15%	113.6	95.0 x 120.0 x 37.0	345.0
CET-90-B	1	90	± 15%	136.0	95.0 x 120.0 x 37.0	375.0